



US009638353B2

(12) **United States Patent**
Francies, III

(10) **Patent No.:** **US 9,638,353 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **CLIP FOR SUPPORTING A PRESTRESSED CABLE ALONG A DOVETAIL SLOT IN A CEMENT CASTING**

(71) Applicant: **Sidney E. Francies, III**, Lithia, FL (US)

(72) Inventor: **Sidney E. Francies, III**, Lithia, FL (US)

(73) Assignee: **A.L. Patterson, Inc.**, Fairless Hills, PA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 35 days.

(21) Appl. No.: **14/931,407**

(22) Filed: **Nov. 3, 2015**

(65) **Prior Publication Data**

US 2016/0123501 A1 May 5, 2016

Related U.S. Application Data

(60) Provisional application No. 62/074,300, filed on Nov. 3, 2014.

(51) **Int. Cl.**
E04C 5/16 (2006.01)
F16L 3/02 (2006.01)
E04C 5/08 (2006.01)
E04C 5/20 (2006.01)

(52) **U.S. Cl.**
CPC **F16L 3/02** (2013.01); **E04C 5/08** (2013.01);
E04C 5/16 (2013.01); **E04C 5/168** (2013.01);
E04C 5/20 (2013.01)

(58) **Field of Classification Search**
CPC F16L 3/02; E04C 5/08; E04C 5/168; E04C 5/16; E04C 5/20
USPC 403/384, 386, 396
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,674,476 A * 6/1928 Mathews E04C 5/168
52/686
1,943,677 A * 1/1934 Kearney H01R 4/32
403/396
2,509,513 A * 5/1950 Mast C08K 5/33
524/430
3,006,114 A * 10/1961 Hillberg E04C 5/08
249/205
3,230,678 A * 1/1966 Eriksson E04C 5/08
52/223.13
5,230,295 A * 7/1993 Shell B60P 7/0823
114/218
2004/0232287 A1 * 11/2004 Rosemann F16L 3/02
248/68.1
2006/0091279 A1 * 5/2006 Jones F16L 3/02
248/431
2007/0044423 A1 * 3/2007 Funk E04C 5/20
52/714

(Continued)

FOREIGN PATENT DOCUMENTS

WO WO 2007/056862 * 5/2007 F16L 3/02

Primary Examiner — Michael Safavi

(74) *Attorney, Agent, or Firm* — McGarry Bair PC

(57) **ABSTRACT**

A clip for securing a prestressed cable along a dovetail slot within a cement cast for masonry work. The clip contains a cup receiving the prestressed cable and legs for a fixed attachment to the outside of a dovetail bar. A method of installing the clip includes inserting the clip between the dovetail slot and the prestressed cable and rotating the clip such that the prestressed cable is received within the cup and the legs capture the dovetail slot.

20 Claims, 5 Drawing Sheets

